

Product Data Sheet

Date: 2018/04/19

Special Notices :

The contaminants or other substances removed or reduced by this water treatment system are not necessarily in your water.
"Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system."

Model:

Model No	Faucet Filter
Product Name	Activated Carbon Faucet Filter with Top / Bottom Cap
Size / Description	OD49/ID16/L67mm / Carbon Block Filter with KDF55 & Calcium Sulfite Media

Claiming:

- ✓ Heavy metal reduction
- ✓ Dirt, particles, as small as 5uM by mechanical means
- ✓ Chlorine, Pesticides, Hazardous, Odor & Taste reduction
- ✓ Bacteria resistance
- ✓ Scale Stop.

Features :

- Activated Carbon made from 100% premium coconut shell.
- Efficiency to reduce Chlorine, pesticide & hazardous chemicals.
- Heavy metal reduction, scale stop and bacteria resistance.
- Materials complied with NSF/ANSI 42 requirement.

Specification:

Operation Pressure	10-58psi (0.7 – 4.0 bar)
Operation Temperature	35°F~120°F (2°C~38°C)
Operation Flow Rate	2 LPM
Service lifespan	5,000 L @ 85% chlorine reduction rate

* Life span cavity is tested based on 2ppm chlorine influent with 85% reduction as life definition by W.F. Srl in-house Lab. followed by the test standard NSF42 7.3.3.
* The result of service lifespan and pressure drop could be varied in field.



Faucet Filter
OD49 x L67mm